

Compactly completeness and finitarily completeness on continuous information system

Mohammed . M. Khalaf and Mohammed M. Ali Al-Shamiri*

Faculty of Engineering, Arab Academy for Science & Technology and

Maritime Transport (AASTMT), Aswan Branch, Egypt.

Department of Mathematics, Faculty of science and arts ,Muhayl Asser, King Khalid University , K.S.A.

Department of Mathematics and Computer, Faculty of Science, Ibb University ,Ibb, Yemen

Abstract

The plane here, introduce and study the concepts of bounded completeness and finitely completeness on continuous information system. Further more compactly completeness, finitarily completeness and strongly compactly completeness for continuous information system. Some interactions between these concepts are investigated. Some corresponding results in posets and domains due to R.Hechmann [5] are generalized.

Key Words : continuous information system , compactly completeness, finitarily completeness, poset

2010 Mathematics subject classification : 03E72; 18B30; 54A40

1 Introduction:

In [5], the concepts of bounded complete posets, bounded complete domains, finitely complete posets, finitely complete domains. It worth to mention that H. Zhang [18] studied some interactions between bounded complete domains and scott-topology and lawson topology. It is interset to mention that in 1994 [1], S. Abramsky and A. Jung considered the concepts of continuous directed complete posets (continuous domain) and algebraic domains. R. Hekmann considered and studies these concepts in detail in this paper [5]. Continuous posets were introduced and studied independently by R. E. Hoffmann [2,6,7,8], J. D. Lawson [11,12] and in more fashion by G. Markowsky [14] and M. Erne [3]. It is worth to mention that J. Nino-Salcedo, considered and studied in more details. Our aims here is devoted to introduce and study concepts of bounded completeness and finitely completeness on continuous information system.

Further more compactly completeness, finitarily completeness and strongly compactly completeness for continuous information system. Some interactions between these concepts are investigated. Some corresponding results in posets and domains due to R.Hechmann [5] are generalized.

Definition 1.1. Let $A \subseteq X$. Then:

(1) The lower (resp. upper) bounded subset in X of λ is denoted by $lb(\lambda)$ (resp. $ub(\lambda)$) and defined as follows:

$$lb(\lambda) = \{x \in X : \forall y \in \lambda, x \leq y\} \text{ (resp. } ub(\lambda) = \{x \in X : \forall y \in \lambda, y \leq x\}.$$

(2) The subset of least (resp. largest) elements of a subset λ is denoted by $le(\lambda)$ (resp. $la(\lambda)$) and defined as follows:

$le(\lambda) = \{x \in \lambda : \forall y \in \lambda, x \leq y\}$ (resp. $la(\lambda) = \{x \in \lambda : \forall y \in \lambda, y \leq x\}$). Each element in $le(\lambda)$ (resp. $la(\lambda)$) is called a least (resp. largest) element of λ [13].

(3) The infimum (resp. supremum) subset in X is denoted by $\bigwedge(\lambda)$ (resp. $\bigvee(\lambda)$) and defined as follows:

$\bigwedge(\lambda) = la(lb(\lambda))$ (resp. $\bigvee(\lambda) = le(ub(\lambda))$). Each element in $\bigwedge(\lambda)$ (resp. $\bigvee(\lambda)$) is called a infimum (resp. supremum) element of λ [13].

(4) The lower (resp. upper) closure in X of λ is denoted by $\downarrow \lambda$ (resp. $\uparrow \lambda$) and defined as follows: $\downarrow \lambda = \{x \in X : \exists y \in \lambda \text{ s.t. } x \leq y\}$ (resp. $\uparrow \lambda = \{x \in X : \exists y \in \lambda \text{ s.t. } y \leq x\}$)[5];

(5) An upper (resp. a lower) cone of X iff $\exists x \in \lambda \text{ s.t. } \lambda = \uparrow x$ (resp. $\lambda = \downarrow x$)[5].

Proposition 1.1. (Proposition 5.2.1 [5]) For a poset (X, \leq) , the following statements are equivalent:

- (1) X is upper cone, and $\forall x, y \in X$, then the set $\uparrow x \cap \uparrow y$ is empty or an upper cone;
- (2) X has a least element, and every two points with a common upper bound have a common least upper bound;
- (3) The set of upper bounds of a finite set is either empty or an upper cone; and
- (4) Every finite bounded subset of X has a supremum.

Poset with each of these equivalent properties are called bounded complete.

Proposition 1.2. (Proposition 5.2.2 [5]). For a poset (X, \leq) , the following statements are equivalent:

- (1) Every bounded subset of X has a supremum. and;
- (2) Every nonempty subset of X has a infimum..

Proposition 1.3. (Proposition 5.2.3 [5]). For a domain X , the statements in Proposition 2.1 and Proposition 2.2 above are equivalent. Every domain satisfies one of these statements is called a bounded complete domain.

Proposition 1.4. (Proposition 5.2.4 [5]). Arbitrary products of bounded complete domains are bounded complete domains.

Proposition 1.5. (Proposition 5.3.1 [5]). For a poset (X, \leq) , the following statements are equivalent:

- (1) X is upper cone, and $\forall x, y \in X$, then the set $\uparrow x \cap \uparrow y$ is empty or an upper cone;
- (2) X has a least element, and every two points have a common least upper bound;

- (3) The set of upper bounds of a finite set is an upper cone; and
- (4) Every finite subset of X has a supremum.

Proposition 1.6. (Proposition 5.3.2 [5]). For a poset (X, \leq) , the following statements are equivalent:

- (1) X is finitely complete domain;
- (2) All finite and all directed subset of X have supermum;
- (3) Every subset of X has a supremum;
- (4) Every subset of X has a infimum; and
- (5) X is bounded complete domains with greatest element.

We call posets which satisfies one of these equivalent properties finitely complete domains. The complete domain is also known as a complete lattice.

Proposition 1.7. (Proposition 5.4.1 [5]). For a poset (X, \leq) , the following statements are equivalent:

- (1) The set of upper bounds f every finite set is finitary;
- (2) X is finitary, and for every two points x and y , the set $\uparrow x \cap \uparrow y$ is finitary;
- (3) X is finitary, and intersection of two finitary upper sets is finitary; and
- (4) Finite intersection of finitary sets are finitary.

A poset satisfying one of these equivalent conditions is said to have finitarily complete.

Proposition 1.8. (Proposition 5.4.2 [5]). In a poset (X, \leq) , the following statements are equivalent:

- (1) Every finite poset is finitarily complete; and
- (2) Every bounded copmlete poset is finitarily complete.

Proposition 1.9. (Proposition 5.4.3 [5]). If X and Y are finitarily set, then $X \times Y$ is finitary set.

Proposition 1.10. (Proposition 4.7.4 [5]). If A and B are strongly compact, then $A \cup B$ so is.

Proposition 1.11. (Proposition 5.5.1 [5]). For a domain X , the following statements are equivalent:

- (1) X is strongly compac; and $\forall x, y \in X$, then the set $\uparrow x \cap \uparrow y$ is strongly compact; and
- (2) X is finitary and the intersection of two finitary upper sets is strongly compact.

Domains with these equivalent properties are called strongly compactly complete.

Definition 1.2. Let ' \leq' ' be a binary relation set on $X \neq \phi$. Then;

- (1) ' \leq' ' is called reflexive iff $\forall x \in X, x \leq x$ [13];
- (2) ' \leq' ' is called antisymmetric iff $\forall x, y \in X, x \leq y$ and $y \leq x \Rightarrow x = y$ [13];
- (3) ' \leq' ' is called transitive iff $\forall x, y, z \in X, x \leq y$ and $y \leq z \Rightarrow x \leq z$ [13];
- (4) ' \leq' ' is called symetric iff $\forall x, y \in X, x \leq y \Rightarrow y \leq x$ [13];
- (5) ' \leq' ' is called interpolative iff $\forall x, z \in X, \text{ with } x \leq z, \exists y \in X \text{ s.t. } x \leq y \leq z$ [5, 16].
- (6) if ' \leq' 'satisfies the conditions (1), (2) and (3), then (X, \leq) is called Partialy order set (Poset) [13];
- (7) if ' \leq' 'satisfies the conditions (1), and (3), then (X, \leq) is called pre-orderd set (Quasi set)[13];
- (8) if ' \leq' 'satisfies the conditions (1), (2), (3) and (4), then (X, \leq) is called an equivalence set,
- (9) if ' \leq' 'satisfies the conditions (3) and (5), then (X, \leq) is a continuous information system [10,16].

(10) if (X, \leq) satisfies the conditions (3), and $\forall x \in X$, and for every finite subset λ of X the following axiom holds: if $\forall y \in \lambda, y \leq x$ then $\exists z \in X$ s.t. $\forall y \in \lambda, y \leq z$ and $z \leq x$, then (X, \leq) is abstract basis [17].

Definition 1.3. (1) A poset (X, \leq) is called domain iff for every directed subset λ of X , $\bigvee(\lambda)$ exists [5].

(2) λ is called directed subset of X iff $\lambda \neq \phi$ and $\forall x, y \in \lambda, \exists z \in \lambda$ s.t. $x \leq z$ and $y \leq z$ [5];

Definition 1.4. Let $A \subseteq X$. Then:

(1) A subset A of the domain [3] (resp. Poset) X is called directed closed (d -closed for short) iff \forall directed subset D of A , $\bigvee(D) \in A$;

(2) A subset A of the Poset X is called Scott-closed iff A is d -closed lower subset of X [11];

(3) A is called d -(resp. Scott-) open iff A^c d -(resp. Scott-) closed [3,11];

Definition 1.5. For any poset X consider the following topologies:

(1) $\delta_d = \{A \subseteq X : A \text{ is } d\text{-open}\}$ is a topology on X (see proposition 3.5.2 [3]) in the case of X is a domain) and is called the directed topology (d -topology for short);

(2) $\delta_{A|x} = \{A \subseteq X : A \text{ is an upper subset}\}$ is a topology on X ([3]) in the case of X is a domain) and is called the Alexandroff topology (Alex-topology for short);

(3) $\delta_S = \{A \subseteq X : A \text{ is Scott open subset}\}$ is a topology on X (see [3,6,11]) and is called the Scott-topology);

(4) The upper topology on X is denoted by δ_U and is the topology generated by subbasis $\{X - \downarrow x : x \in X\}$ [6];

(5) The Lower topology on X is denoted by δ_L and is the topology generated by subbasis $\{X - \uparrow x : x \in X\}$ [6];

(6) The interval topology δ_I on X is the supremum of δ_U and δ_L i.e., $\delta_I = \delta_U \vee \delta_L$ [6];

(7) The Lawson topology δ_{LS} on X is the supremum of δ_S and δ_L i.e., $\delta_{LS} = \delta_L \vee \delta_S$ [6].

(8) Let (X, δ) be a topological space, and let $A \subseteq X$, then the closure of λ denoted by $cl_\delta(\lambda)$ defined as follows $cl_\delta(\lambda) = \bigcap \{F \subseteq X : F \text{ is } \delta\text{-closed and } \lambda \subseteq F\}$ [9].

Proposition 1.5 (Proposition 4.6.8 [5]). Let (X, \leq) be a domain. Then every compact open set in (X, δ_S) is finitary.

Definition 1.6.[5] Let (X, \leq) be a poset. A subset λ of X is called finitary iff \exists a finite subset F of A with $\lambda \subseteq \uparrow(F)$

Definition 1.7. [5] Let (X, \leq) be a poset. A subset $A \subseteq X$ is called strongly compact iff $\forall \bigcirc \in \delta_S$ with $A \subseteq \bigcirc, \exists$ a finitary set F with $A \subseteq F \subseteq \bigcirc$.

2. Bounded complete continuous information system and bounded complete domain continuous information system

Definition 2.1. An continuous information system (X, \leq) is bounded complete iff X is upper cone, and $\forall x, y \in X, ub(\{x, y\})$ is empty or an upper cone.

Theorem 2.1. For a continuous information system (X, \leq) , the following statements are equivalent:

- (1) X is bounded complete continuous information system;
- (2) $le(X) \neq \phi$ and $\forall x, y \in X$, with $ub(\lambda) = (\{x, y\}) \neq \phi$, $\bigvee(\{x, y\}) \neq \phi$;
- (3) If λ is a finite bounded subset from above, then $\bigvee(\lambda) \neq \phi$; and
- (4) If λ is a finite subset of X , then $ub(\lambda)$ is either ϕ or an upper cone.

Proof (1) \Rightarrow (2) : Because X is bounded complete, then X is an upper cone, and $\exists a \in X$ s.t., $\uparrow a = X$. So, $\{\lambda\} \subseteq lb(X)$. If $ub(\{x, y\}) \neq \phi$, then $ub(\{x, y\})$ is an upper cone. There exists $\mu \in ub(\{x, y\})$ s.t., $\uparrow \mu = ub(\{x, y\})$. So, $\mu \in lb(ub(\{x, y\}))$, i.e., $\bigvee(\{x, y\}) \neq \phi$;

(2) \Rightarrow (3) : ϕ is a finite bounded subset from above, Since $ub(\phi) = X \neq \phi$. Since $le(X) = le(ub(\phi)) \neq \phi$, $\bigvee(\phi) \neq \phi$. Let λ be a non-empty finite bounded subset from above. If $\lambda = \{z\}$ and $ub(\{z\}) \neq \phi$, then $\bigvee(\lambda) \neq \phi$. Let $\lambda = \{x_1, x_2, x_3, \dots, x_n\}$ and $ub(\lambda) \neq \phi$. Now $\lambda_{1,2} = \{x_1, x_2\}$ and $ub(\lambda_{1,2}) \neq \phi$, $\bigvee(\lambda_{1,2}) \neq \phi$. Take $u_{1,2} \in \bigvee(\lambda_{1,2})$ and consider $\lambda_{1,2,3} = \{u_{1,2}, x_3\}$. Then $\bigvee(\lambda_{1,2,3}) \neq \phi$. because $ub(\lambda_{1,2,3}) \neq \phi$. We can proceed until consider the set $\mu = \{u_{1,2}, \dots, u_{n-1}, x_n\}$. Since $ub(\mu) \neq \phi$, then $\bigvee(\mu) \neq \phi$. Now $\forall l \in \bigvee(\mu)$, $l \in ub(\lambda)$. Since $m \in ub(\lambda)$, one can deduce that $l \leq m$. Then $l \in \bigvee(\lambda)$. So, $\bigvee(\lambda) \neq \phi$;

(3) \Rightarrow (4) : Let λ be a finite subset of X . If λ is not bounded from above, then $ub(\lambda) = \phi$. Let λ is a finite bounded subset from above. Then $\bigvee(\lambda) = le(ub(\lambda)) \neq \phi$. Then $\exists x \in ub(\lambda)$ s.t., $\uparrow x = ub(\lambda)$;

(4) \Rightarrow (1) : Now, $X = ub(\phi)$ and so X is an upper cone. Since $\forall x, y \in X$, $\{x, y\}$ is finite. Then $ub(\{x, y\}) = \phi$ or $ub(\{x, y\})$ is an upper cone. .

Note 2.1. We refer that Theorem 2.1 is a generalization of the corresponding result in Proposition 1.1 (Proposition 5.2.1 [5]).

The following Lemma is a generalization of the corresponding result in Proposition 1.2 (Proposition 5.2.2 [5]).

Lemma 2.1. For a continuous information system (X, \leq) , the following statements are equivalent:

- (1) If λ is a finite bounded subset from above, then $\bigvee(\lambda) \neq \phi$; and
- (2) If λ is a non-empty subset of X , then $\bigwedge(\lambda) \neq \phi$.

Proof (1) \Rightarrow (2) : Let λ is a non-empty subset of X and let $\mu = lb(\lambda)$, Now $ub(\mu) \supseteq \lambda \neq \phi$. Then $\bigvee(\mu) \neq \phi$; let $x \in \bigvee(\mu)$. Now, $x \in ub(\mu)$. Then $\forall a \in \lambda$, $x \leq a$. Then $x \in la(lb(\lambda)) = \bigwedge(\lambda)$. Hence $\bigwedge(\lambda) \neq \phi$.

(2) \Rightarrow (1) : Let λ is a finite bounded subset of X from above. and let $\mu = ub(\lambda) \neq \phi$. Then $\bigwedge(\mu) \neq \phi$; let $x \in \bigwedge(\mu)$. Since, $\lambda \subseteq lb(\mu)$ and $x \in \bigwedge(\mu)$, then $\forall a \in \lambda$, $a \leq x$. So, $x \in le(ub(\lambda)) = \bigvee(\lambda)$. Hence $\bigvee(\lambda) \neq \phi$.

Definition 2.2. An continuous information system (X, \leq) is bounded complete domain iff it is bounded complete and domain.

Theorem 2.2. For a domain continuous information system (X, \leq) , the following statements are equivalent:

- (1) X is bounded complete continuous information system;
- (2) $le(X) \neq \phi$ and $\forall x, y \in X$, with $ub(\lambda) = (\{x, y\}) \neq \phi$, $\bigvee(\{x, y\}) \neq \phi$;

- (3) If λ is a finite bounded subset from above, then $\bigvee(\lambda) \neq \phi$;
- (4) If λ is a finite subset of X , then $ub(\lambda)$ is either ϕ or an upper cone;
- (5) If λ is bounded subset from above, then $\bigvee(\lambda) \neq \phi$; and
- (6) If λ is a non-empty subset of X , then $\bigwedge(\lambda) \neq \phi$.

Proof We refer that Theorem 2.1 and Lemma 2.1, it rests to proof that (3) and (5) are equivalent.

(3) \Rightarrow (5) : Let λ be bounded subset of X from above. Let $D = \{x : x \text{ is fixed point of } \bigvee F \text{ for every finite subset } F \text{ of } \lambda\}$. Since $\bigvee(\phi) = \phi$ and $\forall y \in \bigvee(F_1 \cup F_2), y \in ub(\bigvee(F_1) \cup (\bigvee(F_2)))$, where F_1, F_2 are finite subsets of λ then is directed. Then $\bigvee(D) = \phi$. Now $\forall l \in \bigvee(D), l \in ub(\lambda)$. Let $z \in ub(\lambda)$. Then $\forall m \in \lambda, m \leq z$, so $z \in ub(\lambda)$ Thus $l \leq z$ so that $l \in \bigvee(\lambda)$. Hence $\bigvee(D) \subseteq \bigvee(\lambda)$ so that $\bigvee(\lambda) \neq \phi$.

(5) \Rightarrow (3) : Obvious.

Note 2.2. We refer that Theorem 2.2 is a generalization of the corresponding result in Proposition 1.3. (Proposition 5.2.3 [5]).

Definition 2.3. [13] Let $(X_i, \leq_i : i \in I)$ be a family of posets. The Cartesian product relation ' \leq' ' on $\prod_{i \in I} X_i$ of $\{\leq_i : i \in I\}$ is defined as follows: $(x_i)_{i \in I} \leq (y_i)_{i \in I}$ iff $x_i \leq_i y_i \forall i \in I$

Theorem 2.3. Let $(X_i : i \in I)$ be a family of continuous information system. If $\forall i \in I, X_i$ is bounded complete domain, then $\prod_{i \in I} X_i$ so is.

Proof Let λ be a subset of $\prod_{i \in I} X_i$. bounded from above by a point $u = (u_i)_{i \in I}$. Let $\lambda_i = \prod \lambda_i \forall i \in I$. Then λ_i is a bounded subset of X_i from a bove by u_i , $\forall i \in I$. Then $\bigvee(\lambda_i) \neq \phi \forall i \in I$. Let $k_i \in \bigvee(\lambda_i) \forall i \in I$ so that $(k_i)_{i \in I} \in \bigvee(\lambda)$. Hence from Theorem 2.2, $\prod_{i \in I} X_i$.is bounded complete domain.

Note 2.3. We refer that Theorem 2.3 is a generalization of the corresponding result in Proposition 1.4. (Proposition 5.2.4 [5]).

3. Finitely complete continuous information system and bounded complete domain continuous information system

Definition 3.1. An continuous information system (X, \leq) is finitely complete iff X is upper cone, and $\forall x, y \in X, ub(\{x, y\})$ is an upper cone.

One can easily deduce that any Finitely complete continuous information system is a bounded complete continuous information system.

Theorem 3.1. For a continuous information system (X, \leq) , the following statements are equivalent:

- (1) X is finitely complete continuous information system;
- (2) X has a least element and $\forall x, y \in X, \bigvee(\{x, y\}) \neq \phi$;
- (3) If λ is a finite subset of X , then $\bigvee(\lambda) \neq \phi$; and
- (4) If λ is a finite subset of X , then $ub(\lambda)$ is an upper cone.

Proof (1) \Rightarrow (2) : Since X is an upper cone, and $\exists a \in X$ s.t., $\uparrow a = X$. So, $a \in le(X)$. let $x, y \in X$. Then $\exists z \in ub(\{x, y\})$ s.t. $\uparrow z \in ub(\{x, y\})$. So, $z \in \bigvee(\{x, y\})$;

(2) \Rightarrow (3) : ϕ is a finite set, Since $\exists x \in le(X)$, then $\exists x \in \bigvee(\phi)$. Let $\lambda = \{x_1, x_2, x_3, \dots, x_n\}$, i.e., λ is a finite set. Now, $\lambda_{1,2} = \{x_1, x_2\}$, then $\exists u_{1,2} \in \bigvee(\lambda_{1,2})$. Put $\lambda_{1,2,3} = \{u_{1,2}, x_3\}$ so that $\exists u_{1,2,3} \in \bigvee(\lambda_{1,2,3})$. We can proceed until consider the set $\mu = \{u_{1,2,3, \dots, n-1}, x_n\}$ so that $\exists l \in \bigvee(\mu)$. Then $l \in ub(\lambda)$. Let $m \in ub(\lambda)$. one can deduce that $l \leq m$. Then $l \in \bigvee(\lambda)$.

(3) \Rightarrow (4) : Let λ be a finite subset of X , then $\bigvee(\lambda) = \phi$. i.e., $\exists l \in le(ub(\lambda))$ so that $\uparrow l = ub(\lambda)$; i.e., $ub(\lambda)$ is an upper cone;

(4) \Rightarrow (1) : Since ϕ is a finite set, and $X = ub(\phi)$, then λ is an upper cone. For every $\{x, y\} \in X$, the set $\{x, y\}$ is finite, then $ub(\{x, y\})$ is an upper cone.

Note 3.1. We refer that Theorem 3.1 is a generalization of the corresponding result in Proposition 1.5 (Proposition 5.3.1 [5]).

Definition 3.2. An continuous information system (X, \leq) is complete domain iff X is finitely complete and domain.

Theorem 3.2. For a continuous information system (X, \leq) , the following statements are equivalent:

- (1) X is complete domain;
- (2) X is bounded complete domain with $la(X) \neq \phi$;
- (3) If λ is a finite subset of X , then $\bigwedge(\lambda) \neq \phi$; and
- (4) If λ is a finite subset of X , then $\bigvee(\lambda) \neq \phi$; and
- (5) If λ is a finite subset of X or a directed subset of X , then $\bigvee(\lambda) \neq \phi$.

Proof (1) \Rightarrow (2) : It is clear that any complete domain is bounded complete domain. Since $\forall x, y \in X$. $ub(\{x, y\})$ is an upper cone so that $ub(\{x, y\}) \neq \phi$. Then X is directed which implies that $la(X) = \bigvee(\lambda) \neq \phi$;

(2) \Rightarrow (3) : Let λ be a finite subset of X . First, if $\lambda = \phi$, then $lb(\phi)$. Since $le(X) \neq \phi$, then $\exists l \in \bigwedge(\phi)$. Second, if $\lambda \neq \phi$, then from Theorem 2.1(6) $\bigwedge(\phi) \neq \phi$.

(3) \Rightarrow (4) : Let λ be a finite subset of X , Since $\bigwedge(\phi) = \phi$. i.e., $\exists l \in la(\lambda)$ so that every subset of X is bounded from above. From Lemma 2.1, $\bigvee(\lambda) \neq \phi$;

(4) \Rightarrow (5) : Obvious; and

(5) \Rightarrow (1) : Since for every directed subset λ of X , $\bigvee(\lambda) \neq \phi$, then X is a continuous information system. From Theorem 3.1(3), X is a finitely complete continuous information system.

Note 3.2. We refer that Theorem 3.2 is a generalization of the corresponding result in Proposition 1.6 (Proposition 5.3.2 [5]).

4. Finitarily complete continuous information system and compactly complete continuous information system

Definition 4.1. Let (X, \leq) be a continuous information system. A subset λ of X is called finitary iff \exists a finite subset F of A with $\lambda \subseteq \uparrow(F)$

Theorem 4.1. Let (X, \leq) be a continuous information system. and let $\{\lambda_i : i \in \{1, 2, 3, \dots, n\}\}$ be a family of finitary subset of X . . Then $\bigcup_j = 1^n \lambda_j$ is a finitary subset.

Proof Since $\forall i \in \{1, 2, 3, \dots, n\}$, \exists a finite subset K_i s.t., $K_i \subseteq \lambda_i \subseteq \uparrow(K_i)$, then

$\bigcup_{j=1}^n K_i \subseteq \bigcup_{j=1}^n \lambda_i \subseteq \bigcup_{j=1}^n \uparrow(K_i) \subseteq \uparrow \bigcup_{j=1}^n (K_i)$. Since $\bigcup_{j=1}^n K_i$ is finite, then it is clear that $\bigcup_{j=1}^n \lambda_i$ is finitary.

Definition 4.2. A continuous information system. (X, \leq) is called finitarily complete iff X is called finitary, $\forall x, y \in X$, $ub(\{x, y\})$ is finitary.

Theorem 4.2. For a continuous information system (X, \leq) , the following statements are equivalent:

- (1) X is finitarily complete;
- (2) X is finitary and if λ and μ are finitary upper sets, then $\lambda \cap \mu$ is finitary;
- (3) If $\lambda_1, \dots, \lambda_n$ are finitary subsets, then $\bigcap_{i=1}^n \lambda_i$ is finitary;
- (4) If μ is a finite subset of X , then $ub(\mu)$ is finitary.

Proof (1) \Rightarrow (2) : If is finitarily complete, then X is finitary. If λ is finitary upper set, then there exists a finite set $F_1 \subseteq \lambda$ s.t., $\lambda \subseteq \uparrow(F_1)$ and $\uparrow \lambda \subseteq \lambda$. Hence $\lambda = \uparrow(F_1)$ and if μ is finitary upper set, then there exists a finite set $F_2 \subseteq \mu$ s.t., $\mu \subseteq \uparrow(F_2)$ and $\uparrow \mu \subseteq \mu$. Hence $\mu = \uparrow(F_2)$. Thus

$\lambda \cap \mu = \uparrow(F_1) \cap \uparrow(F_2) = \left(\bigcup_{a \in F_1} \uparrow a \right) \cap \left(\bigcup_{b \in F_2} \uparrow b \right) = \bigcup_{a \in F_1, b \in F_2} (\uparrow a \cap \uparrow b)$, i.e., $\lambda \cap \mu$ is a finite union of finitary sets. So that $\lambda \cap \mu$ is a finitary;

(2) \Rightarrow (3) : By indication. The empty intersection is X ;

(3) \Rightarrow (4) : If μ is a finite, then $ub(\mu) = \left(\bigcup_{e \in B} \uparrow e \right)$. upper cones are finitary;

(4) \Rightarrow (1) : X is the set of upper bounds of ϕ , and $\uparrow x \cap \uparrow y$ is the set of upper bounds of $\{x, y\}$.

Note 4.1. We refer that Theorem 4.2 is a generalization of the corresponding result in Proposition 1.7. (Proposition 5.4.1 [5]).

Theorem 4.3. Let (X, \leq) be a continuous information system, then;

- (1) Every finite continuous information system is finitarily complete; and
- (2) Every bounded complete continuous information system is finitarily complete continuous information system.

Proof Follow directly from Theorem 2.2 and the fact all finite sets are finitary.

Note 4.2. We refer that Theorem 4.3 is a generalization of the corresponding result in Proposition 1.8. (Proposition 5.4.2 [5]).

Theorem 4.4. Let (X, \leq) be a continuous information system. If X and Y are finitarily complete, then $X \times Y$ so is.

Proof Product of finitary sets are finitary. Hence $X \times Y$ is finitary. furthermore,

$$\uparrow(x_1, y_1) \cap \uparrow(x_2, y_2) = (\uparrow x_1 \times \uparrow y_1) \cap (\uparrow x_2 \times \uparrow y_2) = (\uparrow x_1 \cap \uparrow x_2) \times (\uparrow y_1 \cap \uparrow y_2) \text{ holds.}$$

The final outcome is finitary as product of finitary sets.

Note 4.3. We refer that Theorem 4.4 is a generalization of the corresponding result in Proposition 1.9. (Proposition 5.4.3 [5]).

Definition 4.3. Let (X, \leq, δ) be a topological continuous information system. A subset λ of X is called strongly compact $\forall \bigcirc \in \delta$ s.t., $\lambda \subseteq \bigcirc$, \exists a finitary subset F with $\lambda \subseteq F \subseteq \bigcirc$.

Theorem 4.5. Let (X, \leq, δ) be a topological continuous information system such that each member of δ is an upper subset. If a subset λ of X is strongly compact, then λ is compact.

Proof Let U be an open cover of λ , i.e., $\lambda \subseteq \bigcup_{\mu \in U} \mu$ and $U \subseteq \delta$. Put $\bigcup_{\mu \in U} \mu = G$. Then $\lambda \subseteq G \subseteq \delta$. Since λ of X is strongly compact, then there exists a finitary subset K of G s.t., $\lambda \subseteq K \subseteq G$ so that there exists a finite subset F of K s.t., $K \subseteq \uparrow(F)$, Then $\forall x \in F$, $\exists B_x \in U$ s.t., $x \in B_x$ so that $F \subseteq \bigcup_{x \in F} B_x$ so that $\lambda \subseteq K \subseteq \uparrow(F) \subseteq \uparrow(\bigcup_{x \in F} B_x) = \bigcup_{x \in F} B_x$. Hence λ is compact.

Corollary 4.1. (1) Let $\delta_{A|x}$ is Alexandroff topology induced by $' \leq'$, let λ of X is strongly compact, then λ is compact,

(2) Let δ_S is Scott- topology induced by $' \leq'$, let λ of X is strongly compact, then λ is compact

Theorem 4.6. Let (X, \leq, δ) be a topological continuous information and let $\{\lambda_i : i \in \{1, 2, 3, \dots, n\}\}$ be a strongly compact subsets of X . Then $\bigcup_{i=1}^n \lambda_i$ is strongly compact subsets of X .

Proof Let $\bigcirc \in \delta$ s.t., $\bigcup_{i=1}^n \lambda_i \subseteq \bigcirc$. Then $\forall i \in I$, \exists a finitary subset K_i s.t. $\lambda_i \subseteq K_i \subseteq \bigcirc$ so that $\bigcup_{i=1}^n \lambda_i \subseteq \bigcup_{i=1}^n K_i \subseteq \bigcirc$. From Theorem 4.1 $\bigcup_{i=1}^n K_i$ is finitary, then $\bigcup_{i=1}^n \lambda_i$ is strongly compact.

Note 4.4. We refer that Theorem 4.6 is a generalization of the corresponding result in Proposition 1.10. (Proposition 4.7.4 [5]).

Definition 4.4. Let (X, \leq, δ) be a topological continuous information system. A subset λ of X is called strongly compact complete continuous information system iff X is strongly compact and let $\forall x, y \in X$, $ub(\{x, y\})$ is strongly compact.

Theorem 4.7. Let (X, \leq, δ) be a continuous information system, If

- (1) X is strongly compactly complete; and
- (2) X is finitary and the intersection of two finitary upper sets is strongly compact. Then

- (i) (1) \Rightarrow (2),
- (ii) If ' \leq' is reflexive, (2) \Rightarrow (1).

Proof (i) Since X is strongly compact and open, then there exists a finitary μ of X s.t. $X \subseteq \mu \subseteq X$ so that X is finitary. Let λ and μ be two finitary upper sets. Then there are finite sets E and F s.t. $\lambda \subseteq \uparrow(E) \subseteq \uparrow(\lambda) \subseteq \lambda$ and $\mu \subseteq \uparrow(F) \subseteq \uparrow(\mu) \subseteq \mu$. So $\lambda \subseteq \uparrow(E)$ and $\mu \subseteq \uparrow(F)$. Now $\lambda \cap \mu \subseteq \uparrow(E) \cap \uparrow(F) = \bigcup_{e \in E, f \in F} (\uparrow e \cap \uparrow f)$ so that, from Theorem 4.6, $\lambda \cap \mu$ is strongly compact.

(ii) Since X is finitary and the only open set containing X , then X is strongly compact. Let $x, y \in X$, since ' \leq' is reflexive, $\forall x \in X$, $\uparrow x$ is finitary and since ' \leq' transitive, then $\uparrow x$ is upper set. Hence $\uparrow x \cap \uparrow y$ is strongly compact.

Note 4.4. We refer that Theorem 4.7 is a generalization of the corresponding result in Proposition 1.11. (Proposition 5.5.1 [5]).

Definition 4.5. Let (X, \leq, δ) be a topological continuous information system. X is called compactly complete iff X is compact and let $\forall x, y \in X$, $ub(\{x, y\})$ is compact.

Definition 4.6. Let (X, \leq, δ) be a topological continuous information system. We say that δ has the property F iff every compact open set in (X, δ) is finitary.

Example 4.1 From Proposition 1.5 (Proposition 4.6.8 [5]). In (X, \leq, δ_S) where X is a domain. and δ_S is Scott-topology induced by ' \leq' , δ_S has the property F .

Theorem 4.8. Let (X, \leq, δ) be a continuous information system, If

- (1) X is compactly complete; and
- (2) X is finitary and the intersection of two finitary upper sets is compact. Then
 - (i) If δ has the property F , (1) \Rightarrow (2), and
 - (ii) If ' \leq' is reflexive, and each member of δ is upper set, then (2) \Rightarrow (1).

Proof (i) Since δ has the property F , then X is finitary. Let U and V be two finitary upper sets. Then there are finite sets E and M s.t. $U \subseteq \uparrow(E) \subseteq \uparrow(U) \subseteq U$ and $V \subseteq \uparrow(M) \subseteq \uparrow(V) \subseteq V$. So, $U \subseteq \uparrow(E)$ and $V \subseteq \uparrow(M)$. Now $U \cap V \subseteq \uparrow(E) \cap \uparrow(M) = \bigcup_{e \in E, m \in M} (\uparrow e \cap \uparrow m)$ so that $U \cap V$ is compact. because a finite union of compact subset is compact.

(ii) Since X is finitary, then X is strongly compact. From Theorem 4.5, X is compact. since ' \leq' is reflexive, then $\forall x \in X$, $x \in \uparrow x$ so that $\uparrow x$ is finitary. Furthermore $\forall x \in X$, $\uparrow x$ is upper set. Hence $\forall x, y \in X$, $\uparrow x \cap \uparrow y$ is compact.

5- Conclusion

We have done the research tasks such that the corresponding results of completeness properties in R. Heckmann theorems [5], are strengthened by our results. Also, we can give open problem to the researchers if can get our results

if a binary relation ' \leq' ' be a binary relation set on $X \neq \phi$ have one only condition on Definition 1.2.

No conflict of interest

References

1. S. Abramsky and A. Jung, domain theory in the Handbook for logic in Computer Science, Volume 3, Edited by S. Abramsky, Dov M. Gabbay, and T. S. E. Maibaum, published by Clarendon Press, Oxford in 1994.
2. B. Branachewski and R. E. Hofmann (eds), Continuous lattices, Lecture Notes in Mathematices 871, Springer-Verlag, Berlin, Heidelberg, New York, 1981.
3. M. Erne, Scott convergence and Scott Topologies in Partially ordered sets II, in [BH] [2], pp. 61-96.
4. G. Gierz, K. H. Hofmann, K. Keimel, J. D. Lawson, M. Mislove, and D. s. Scott, A compendium of continuous lattices, Springer Verlag, Berlin, Heidelberg, New York, 1980.
5. R. Heckmann, Power domain constuctions Ph. D. thesis, University Saarlandes, 1999.
(<http://rwt.cs.unisb.de/heckman/diss/diss.html>.)
6. R. E. Hofmann, Continuous Poset comletely distributive complete lattices and Hausdorff compactifications, in [3], pp. 159-208.
7. R. E. Hofmann, Projective sober spaces, continuous lattices, Proc. Conf., Bremen 1979, Lect. Notes Math., 871 (1981), pp. 125-158.
8. R. E. Hofmann, Sobrification of partially ordered sets, Semi-group Forum, Volume 17 (1979) 123-138.
9. R. Kummetz, Partially ordered sets with projections and their topology, pd. D. thesis; Dresden University of Technology, 2000.
10. K. Larsen and G. Winskel, Using information systems to solve recursive domain equations effectively, in G. Kahn, D. B. Mac-Queen and G. Plotkin, eds, Semantics of data types, Lecture Notes in Computer Science 173, Springer -Veralg, Berlin,1984, 109-129.
11. J. D. Lawson, The duality of continuous posets, Houston. J. Math., Volume5, No. 3(1979) 357-386.
12. J. D. Lawson, The Versatile continuous order, in Lecture Notes in Computer Science 298, Springer -Veralg, Berlin, heidelberg, New Yourk, 1987, pp 134-160.
13. S. Lipschutz, Theory and problems of general topology, Schaum series, McJRAW-HILL INT., 1965.
14. G. Markowsky [1981a] , A motivation and generalization of Scott's notion of a continuous lattice, in [1979, Bremen], in [BH] [2], pp. 298-307.
15. J. Nino-Salcedo, On continuous posets and their applications, Ph.D. thesis, Tulane University, 1981.
16. S. Vickers. Information systems for continuous posets, Theoretical Computer Science 114, SIssue 2 (1993)201-299.

17. P. Waszhiewicz, Quantitative continuous domain, Ph.D. thesis School of Computer Science, University of Birmingham Edgbas-ton 2002.
18. Xinyang, FengJian Tang and Bijan DavvazYanfeng Luo, A novel study on fuzzy ideals and fuzzy filters of ordered *-semigroups, Journal of Intelligent and Fuzzy Systems 33(1):423-431 · June 2017
19. Xiang-Yun Xie, Jian Tang and Bijan Davvaz, An investigation on hyper S-posets over ordered semihypergroups, Open Mathematics 15(1) · February 2017
20. H. Zhang, Dualities of domains, Ph. D. thesis, Department of Mathematics, Tulane University, 1993.